


Gas Station Complete Solution








Censtar Science & Technology Corp. Ltd.
 Add: Hi-new Technology Industry Development
 Zone, Zhengzhou City, Henan Province, China
 Tel:+86-371-67989006
 E-mail: sales@censtar.com
 http://www.censtar.com



T MAN Series Fuel Dispenser



HIGH SECURITY SECURED  **WATERPROOF AND DUSTPROOF**

-  6200 Main Board: Latest Electronic Technology, More Safety and Stability
-  Intelligent Voice Broadcast System, Printer Bill System, Full-service Customers
-  Adjustable Display: Brightness can be adjusted according to the light
-  Pos Smart Upgrade Simply Maintenance
-  High-precision Flow Meter: Shell use unique technical processing, moistureproof, rustproof, All the advanced design assure outstanding performance no malfunctions within 5,000,000 liters, life-cycle can reach 10,000,000 liters and wide temperature adoption from -40°C-55°C

Available Options

- International Solenoid Valve
- International Brand Nozzle
- Breakaway and Swivel
- IC Card Payment Terminal
- English Receipt Printer
- Stainless Steel Arm Side and Canopy



Technical Parameters:

- Accuracy: ±0.25%
- Flow Rate Range: 5-50L/Min or 8-80L/Min
- Intake Vacuum: ≥54KPA
- Display: sales 0.00 to 99999999
- Noise: ≤80dB(A)
- Volume: 0.00 to 99999.99
- Unit Price: 0.00 to 99999 (Decimal point position can be chosen)
- Electrical Totalizer: 0.00 to 99999999.99
- Electrical Mechanical Totalizer: 0.00 to 99999999
- Power Supply: AC380V or AC220V with a changing range from -15% to +10%
- Motor's Output Power: 750W and 1000W
- Working Environmental Temperature: -40°C to +55°C
- Relative Humidity: 30% to 90%

T MAN Series Fuel Dispenser



Configuration Table (T MAN)

| | Pump Type | Nozzle | Oil Product | Display | Flow Rate (L/Min) | | |
|----------------------------------|------------------|--------|--------------------------------------|---------|-------------------|------|--|
| | | | | | 5-50 | 8-80 | |
| 1H 1P | Gear Pump | 1 | 1 | 1 | 5-50 | 8-80 | |
| 1H 1P | Submersible Pump | 1 | 1 | 1 | 5-50 | 8-80 | |
| Net Size: 660*470*1440mm (L*W*H) | | | Package Size: 775*550*1465mm (L*W*H) | | | | |